





TORICA[®]-aA / -aAY

| TECHNICAL INFORMATION | | |
|---|--|--|
| TORIC MONOBLOC ACRYLIC ASPHERIC   | TORICA[®]-aA  | TORICA[®]-aAY YELLOW  |
| Type | foldable toric posterior chamber IOL one-piece with C-loop haptics available in Compact line (CL) | |
| Material | hydrophilic acrylic with UV absorber; water content 26% at 35°C, blue-light protection optional, Abbe number 56 | |
| Specifics | toric meridional aspheric anterior surface (aberration free) ⁽¹⁾ posterior surface with 360° lens epithelial cell barrier | |
| Diopter Range | <i>for more details on diopter categories, see page 2</i> | |
| SE in 0.5 D steps | -20.0 to 60.0 D | |
| Cylinder in 0.5 D steps | 1.0 to 30.0 D (-20.5 D ≤ Meridian ≤ 60.5 D) | |
| Cylinder Axis | the two thin diametrically opposed lines in the periphery of the optic indicate the axis of the plus-cylinder | |
| Est. A-const ⁽¹⁾ | Please use for calculation only optimized constants. Constants should be individualized subsequently per surgeon. For more details, please visit www.humanoptics.com | |

⁽¹⁾ The word "aberration" as used in this document refers to "spherical aberration"

DIOPTER CATEGORY - TORICA® -aA / -aAY

CYLINDER [D] →

